XEROX

ISO/IEC 19752 Yield Test Report

USE GENUINE XEROX SUPPLIES MADE FOR EACH OTHER

Phaser 4400 Toner Cartridge (Standard Capacity)

Declaration of Yield:

Published Cartridge Yield: 10,000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average:	10,791
Standard Deviation:	536
90% Lower Confidence:	10,459

"Customer Report, compliant with ISO/IEC 29142"

	Start	End
Date Tested:	3-Feb-2007	7-Mar-2007

Number of Cartridges used in testing:	9
Number of Cartridges used in calculations:	9
Type of Cartridge:	Standard Capacity Cartridge
Shake Procedure Used?	No
Print mode:	Continuous (500pages/job)
Number of engines used in testing:	3
Media Used:	Xerox 4200
Paper Weight:	20lb
Paper Size:	A4
Paper feed orientation:	Long Edge Feed (LEF)
Computer Model:	Dell PC 1.2GHz
Driver Version:	Xerox
Operating System:	Windows XP
Application Software:	Adobe Acrobat Professional 7.0.1
Test Page Version:	ISO/IEC 19752:2004
Power (off/on) everyday?	No

Cartridge	Printer	Temperature (°C)			Humidity (%RH)			Cartridge	Included
Serial Number	Serial Number	Avg.	Max	Min	Avg.	Max	Min	Yield	in calc.
4400 SC1-1	XWO3563	22.6	23.0	22.0	50.0	51.0	49.0	11,230	y
4400 SC1-2	XWO3563	22.6	22.8	22.4	50.0	50.0	50.0	11,410	y
4400 SC1-3	XWO3563	22.4	22.8	22.0	50.0	51.0	49.0	9,900	y
4400 SC1-1	XW03458	22.4	22.8	22.0	50.0	50.0	49.0	10,280	y
4400 SC1-2	XW03458	22.6	22.0	22.4	50.0	51.0	49.0	10,320	y
4400 SC1-3	XW03458	22.5	22.8	22.3	50.0	51.0	49.0	10,560	y
4400 SC1-1	XW03533	22.4	22.8	22.0	50.0	50.0	49.0	11,040	y
4400 SC1-2	XW03533	22.7	22.8	22.5	50.0	51.0	49.0	11,120	y
4400 SC1-3	XW03533	22.5	22.8	22.3	50.0	51.0	49.0	11,260	y

Comments: